

BARRIERE D'ARIA CENTRIFUGHE

Serie Heavy duty



SENZA RESISTENZA

Alimentazione

220/240 1ph 50/60Hz

COD.	Portata aria m ³ /h Min - Max	Potenza assorbita W			Rumorosità dB	Peso Kg.	Dimensioni mm.
		Min - Max	220v 1ph				
ACN-09	900 - 1160	125 - 300	0,6 A		51 - 56	17,5	900x235x207
ACN-10	960 - 1260	135 - 340	0,7 A		51 - 56	19,5	1000x235x207
ACN-12	1260 - 1560	185 - 400	1,0 A		52 - 58	21,5	1200x235x207
ACN-15	1560 - 1960	220 - 500	1,2 A		54 - 60	25,5	1500x235x207
ACN-18	2550 - 2980	265 - 600	1,3 A		58 - 64	29,5	1800x235x207
ACN-20	2550 - 2980	305 - 700	1,5 A		58 - 64	32,5	2000x235x207

CON RESISTENZA

Alimentazione

220/240 1ph 50/60Hz — 380v 3ph 50/60Hz

COD.	Portata aria m ³ /h Min - Max	Potenza assorbita W					Rumorosità Noise dB	Peso Kg.	Dimensioni mm.
		Ventilazione		Resistenze					
		Min	Max	W	220v 1ph	380v 1ph			
ACH-09	960-1120	125	300	7300	25 A	14 A	53-58	18,0	900x260x210
ACH-10	960-1121	135	340	7500	34 A	20 A	53-58	19,0	1000x260x210
ACH-12	1080-1380	185	400	9800	38 A	23 A	55-60	22,5	1200x260x210
ACH-15	1380-1580	220	500	12200	48 A	27 A	57-63	27,5	1500x260x210

H installazione

fino a 4,0 mt.

Velocità aria

Min 9,0 m/s - Med 13,0 - Max 16,0 m/s